



### Stylish 32" VA panel with 4K resolution

The ProLite X3272UHS is a 32" 4K monitor capable of displaying 4 times more information than a Full HD screen. It will hence suit a massive range of applications requiring an above average viewable area, like desktop publishing, CAD/CAM drawing, data virtualization, photographic and web design. The VA panel technology offers exceptional colour performance, high contrast and wide viewing angles. HDMI, DisplayPort, integrated speakers and a headphone socket ensure compatibility across various devices and media platforms.



4K

UHD resolution (3840x2160), better known as 4K, offers a gigantic viewable area with 4 times more information and work space than a Full HD screen. Due to the high DPI (dots per inch), it displays an incredibly sharp and crisp image.



VA

VA panel technology offers higher contrast, darker blacks and much better viewing angles than standard TN technology. The screen will look good no matter what angle you look at it.

## 01 DISPLAY CHARACTERISTICS

Diagonal	31.5", 80cm
Panel	VA LED, matte finish
Native resolution	3840 x 2160 @60Hz (HDMI&DisplayPort, 8.3 megapixel 4K UHD)
Aspect ratio	16:9
Panel brightness	300 cd/m <sup>2</sup>
Static contrast	3000:1
Advanced contrast	50M:1
Response time (GTG)	3ms
Viewing zone	horizontal/vertical: horizontal°/vertical horizontal°, right/left: 0°/0°, up/down: 0°/0°
Colour support	1.07B 10bit (8bit + Hi-FRC) (sRGB: 137%, NTSC: 97%)
Horizontal Sync	30 - 135kHz
Viewable area W x H	695.04 x 390.96mm, 27.4 x 15.4"
Pixel pitch	0.181mm
Colour	matte

## 02 INTERFACES / CONNECTORS / CONTROLS

Signal input	HDMI x2 DisplayPort x1
HDCP	yes
Headphone connector	yes

## 03 FEATURES

Blue light reducer	yes
Flicker free	yes
Extra	PiP
OSD languages	EN, DE, FR, ES, IT, PT, RU, JP, CZ, NL, PL
Control buttons	Power/ Menu, Scroll up, Scroll down/ ECO Mode, Left/ Input Select, Right/ Audio Adjust
User controls	luminance (contrast, brightness, i-Style Colour, ACR, OverDrive), image setup (aspect ratio), colour temperature, OSD setup (H. position, V. position, timeout, language), PIP (PIP setting, size, position, swap), extra (input select, DDC/CI, reset, information)
Speakers	2 x 2W
Convenience	Kensington-lock™ prepared, DDC/CI, DDC2B, Mac OSX

## 04 MECHANICAL

Display position adjustments	tilt
Tilt angle	12° up; 4° down
VESA mounting	100 x 100mm

## 05 ACCESSORIES INCLUDED

Cables	power, HDMI, DP
Other	quick start guide, safety guide

## 06 POWER MANAGEMENT

<b>Power supply unit</b>	internal
<b>Power supply</b>	AC AC - AC V, AC /V, 100Hz
<b>Power usage</b>	52W typical, 0.5W stand by, 0.5W off mode

## 07 SUSTAINABILITY

<b>Regulations</b>	CE, TÜV-Bauart, VCCI-B, PSE, RoHS support, ErP, WEEE, CU, REACH
<b>REACH SVHC</b>	above 0.1%: Lead

## 08 DIMENSIONS / WEIGHT

<b>Product dimensions W x H x D</b>	729.5 x 546 x 254mm
<b>Weight (without box)</b>	6.8kg
<b>EAN code</b>	4948570115754

*All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.*

© IIYAMA CORPORATION. ALL RIGHTS RESERVED