




ProLite LE4340S - profesionalni Full HD ekran velikog formata od 43" sa reprodukcijom USB medija

ProLite LE4340S je 43" profesionalni Full HD LED ekran, dizajniran da radi bez ventilatora. Uključujući najnoviju AMVA tehnologiju, ekran garantuje sjajan pregled iz svih uglova, veliku osvetljenost i izuzetnu jasnoću boja. Širok raspon audio i video ulaza osigurava kompatibilnost povezivanja sa velikim brojem uređaja. ProLite LE4340S je spreman za jednostavno montiranje pomoću zidnog nosača (VESA standard). Ovaj ekran će odgovarati širokom rasponu primena uključujući oglašavanje u javnim prostorima, maloprodaju, izložbene i konferencijske centre, POS / POI, kontrolne sobe i proizvodne prostore.



VA matrica

Tehnologija VA panela nudi veći kontrast, tamnije crne i mnogo bolje uglove gledanja od standardne TN tehnologije. Ekran će izgledati dobro bez obzira pod kojim uglom gledate.



USB Playback

Monitor podržava reprodukciju prezentacija, videa i gotovo bilo koje vrste sadržaja sačuvanih na USB uređaju ili u unutrašnjoj memoriji.

01 KARAKTERISTIKE EKRANA

Dijagonala	43", 108cm
Panel	VA, haze 2%
Osnovna rezolucija	1920 x 1080 (2.1 megapixel Full HD)
Format ekrana	16:9
Osvetljenje	350 cd/m ²
Statički kontrast	3 000:1
Vreme odziva (GTG)	8ms
Zona gledanja	horizontalno/vertikalno: 178°/178°, desno/levo: 89°/89°, gore/dole: 89°/89°
Podržane boje	16.7mln
Horizontalna sinhronizacija	30 - 83KHz
Vidljiva površina Š x V	940.9 x 529.25mm, 37 x 20.8"
Širina okvira (stranice, vrh, dno)	12mm, 12mm, 15mm
Razmak piksela	0.49mm
Boja okvra	crna, sjajna

02 KONEKTORI / KONTROLE

Ulaz analognog signala	VGA x1 Komponentni video x1 (RGB Y(CVBS)/Pb/Pr) RCA Kompozitni x2
Ulaz digitalnog signala	DVI x1 HDMI x1
Audio ulaz	RCA (L/D) x1 Mini konektor x1
Kontrolni ulaz	RS-232c x1 RJ45 (LAN) x1 IR x1
Audio izlaz	RCA (L/R) x1 Zvučnici 2 x 10W
Monitor kontrolni izlaz	RS-232c x1 IC loop x1
HDCP	da
USB portovi	x1 (v.2.0 media playback)

03 KARAKTERISTIKE

Maksimalno neprekidno radno vreme	12/7
Reprodukcija medija	da
Kućište (okvir)	plastika

04 OPŠTE

OSD jezici	EN, DE, FR, ES, IT, RU, JP, CZ, NL, PL
Kontrolni tasteri	Power, Mute, Input, +, -, Up, Down, Menu
Korisničke kontrole	podešavanje slike (režim slike, reset, pozadinsko osvetljenje, kontrast, osvetljenje, nijansa, boja, oština, napredno podešavanje, format i ivice), zvuk (zvučni režim, reset, bas, visoki tonovi, audio izlaz, napredna podešavanja), opšta podešavanja (jezik, ID monitora, ECO način rada, automatsko pretraživanje, sat, zakazivanje, merač vremena mirovanja, automatsko isključivanje, automatsko podešavanje, podšavanja kontrole, logo pri pokretanju, fabrička podešavanja), mrežna podešavanja (pogledajte mrežna podešavanja, mrežna podešavanja, statička IP konfiguracija, render digitalnih medija, wake on LAN, naziv mreže)

Plug&Play	DDC2B, Mac OSX
-----------	----------------

05 MEHANIČKI

Orijentacija	pejzaž
--------------	--------

Dizajniran bez ventilatora	da
----------------------------	----

VESA montiranje	400 x 400mm
-----------------	-------------

Opseg radne temperature (-°/+°)	-0°C - 40°C
---------------------------------	-------------

Temperatura skladištenja	- 20°C - 60°C
--------------------------	---------------

06 UKLJUČENI DODACI

Kablovi	Strujni kabl, VGA, DVI, RS-232c
---------	---------------------------------

Upustva	kratko uputstvo, bezbednosni vodič
---------	------------------------------------

Daljinski upravljač	da
---------------------	----

07 UPRAVLJANJE NAPAJANJEM

Napajanje	interna
-----------	---------

Potrošnja energije	% 1W tipično, 0.5W stand by, 0.5W isključen
--------------------	---

08 ODRŽIVOST

Propisi	CE, TÜV-Bauart, EAC, RoHS podrška, ErP, WEEE, REACH
---------	---

Klasa energetske efikasnosti (Regulation (EU) 2017/1369)	G
--	---

REACH SVHC	iznad 0.1%: Olova
------------	-------------------

09 DIMENZIJE / TEŽINA

Dimenzije proizvoda Š x V x D	968 x 559.5 x 61mm
-------------------------------	--------------------

Dimenzije kutije Š x V x D	1070 x 696 x 159mm
----------------------------	--------------------

Težina (bez kutije)	8.7kg
---------------------	-------

Težina (sa kutijom)	10.75kg
---------------------	---------

EAN kod	4948570114184
---------	---------------



All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

© IYAMA CORPORATION. ALL RIGHTS RESERVED