



34" IPS ultra-wide screen with a height adjustable stand

ProLite XUB3493WQSU is a 34" LED monitor featuring the latest IPS Panel technology considered to be the best all round panel type. It offers accurate and consistent colour reproduction with wide viewing angles and a fast response time. UWQHD (Ultra Wide QHD) resolution offers an ultra wide (21:9) viewable area. The large amount of space and good pixel density offered by the size and resolution of this screen provide great potential on the desktop. Very suitable for those who want to use side-by-side applications, watch a movie shot in widescreen format or enrich their gaming experience.



IPS Technology

IPS technology offers higher contrast, darker blacks and much better viewing angles than standard TN technology. The screen will look good no matter what angle you look at it.



ULTRA WIDE - UWQHD

UWQHD (Ultra Wide QHD) resolution offers an ultra wide (21:9) viewable area.

01 DISPLAY CHARACTERISTICS

Diagonal	34", 86.7cm
Panel	ADS-IPS, matte finish, haze 25%
Native resolution	3440 x 1440 @75Hz (4.9 megapixel UWQHD)
Aspect ratio	21:9
Panel brightness	400 cd/m ²
Static contrast	1000:1
Advanced contrast	80M:1
Response time (GTG)	4ms
Viewing zone	horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Colour support	16.7mIn 8bit (sRGB: 100%, NTSC: 74%)
Horizontal Sync	30 - 115kHz
Viewable area W x H	799.8 x 334.8mm, 31.5 x 13.2"
Pixel pitch	0.233mm
Colour	matte, black

02 INTERFACES / CONNECTORS / CONTROLS

Signal input	HDMI x2 (v.2.0) DisplayPort x1 (v.1.2)
USB HUB	x2 (v.3.0 (DC5V, 900mA))
HDCP	yes
Headphone connector	yes

03 FEATURES

Blue light reducer	yes
Flicker free	yes
Adaptive Sync support	HDMI & Display Port: 3440 x 1440 @48-75Hz
HDR	yes
OSD languages	EN, DE, FR, IT, RU, JP, CZ, NL, PL
Control buttons	Power, Menu, Right/ Volume, Left/ ECO, Input/ Exit
User controls	picture (picture format, brightness, contrast, black tuner, sharpness, OD, ACR, ECO, X-Res Technology), colour adjust (warm, normal, cool, user control, i-Style Colour, Blue Light Reducer), PiP/PbP (PiP/PbP mode, sub win input, PiP size, PiP position, swap), input select, audio (volume, mute, audio input), language, OSD settings (OSD H. position, OSD V. position, OSD background, OSD time out), setup menu (DP format, HDMI RGB range, HDR, FreeSync, opening logo, LED, auto power off, memory recall, information)
Speakers	2 x 5W
Convenience	Kensington-lock™ prepared, DDC/CI, Mac OSX

04 MECHANICAL

Display position adjustments	height, swivel, tilt
Height adjustment	130mm
Swivel stand	90°; 45° left; 45° right
Tilt angle	22° up; 3° down
VESA mounting	100 x 100mm
Cable management system	yes

05 ACCESSORIES INCLUDED

Cables	power, USB, HDMI, DP
Other	quick start guide, safety guide

06 POWER MANAGEMENT


Power supply unit	internal
Power supply	AC 100 - 240V, 50/60Hz
Power usage	43W typical, 0.5W stand by, 0.5W off mode

07 SUSTAINABILITY

Regulations	CE, TÜV-Bauart, EAC, VCCI-B, PSE, RoHS support, ErP, WEEE, REACH, UKCA
Energy efficiency class (Regulation (EU) 2017/1369)	G
REACH SVHC	above 0.1%: Lead

08 DIMENSIONS / WEIGHT

Product dimensions W x H x D	817 x 415 (545) x 230mm
Box dimensions W x H x D	900 x 200 x 460mm
Weight (without box)	9.5kg
Weight (without stand)	6.8kg
Weight (with box)	12.8kg
EAN code	4948570117147



All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

© IIYAMA CORPORATION. ALL RIGHTS RESERVED