



#### Unleash your full gaming potential with the Fast IPS GB2770HSU Red Eagle

Get the competitive edge you need to unleash your full gaming potential with the 27" GB2770HSU offering 0.8ms MPRT and 165Hz refresh rate. Armed with FreeSync Premium you can make split second decisions and forget about ghosting effects or smearing issues. The ability to adjust brightness and the dark shades with the Black Tuner delivers greater viewing performance in shadowed areas and the IPS panel technology guarantees superb image quality. Thanks to the height adjustable stand you can easily adjust the screen position to your preferences to ensure comfort during marathon gaming sessions.

Available also with fixed stand : G-Master G2770HSU-B1 (1920x1080) and G-Master G2770QSU-B1 (2560x1440)



Fast IPS

The Fast IPS panel technology guarantees not only high-fidelity, vivid battleground scenes displayed with outstanding colour accuracy but provides also an outstanding 0.8ms Moving Picture Response Time (MPRT).



FreeSync™ Premium Technology

This monitor guarantees low input latency and low framerate compensation putting an end to any tearing or stuttering issues at virtually any framerate.



Diagonal	27", 68.6cm
Panel	Fast IPS IGZO, matte finish
Native resolution	1920 x 1080 @165Hz (2.1 megapixel Full HD, DisplayPort)
Aspect ratio	16:9
Panel brightness	250 cd/m <sup>2</sup>
Static contrast	1100:1
Advanced contrast	80M:1
Response time (MPRT)	0.8ms
Viewing zone	horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Colour support	16.7mln 8bit
Horizontal Sync	15 - 225kHz
Viewable area W x H	598 x 336.5mm, 23.5 x 13.2"
Pixel pitch	0.311mm
Colour	matte, black



### 02 INTERFACES / CONNECTORS / CONTROLS

Signal input	HDMI x1 (max. 1920 x 1080 @144Hz) DisplayPort x1 (max. 1920 x 1080 @165Hz)
USB HUB	x2 (v.2.0 DC5V, 500mA)
HDCP	yes
Headphone connector	yes



# 03 FEATURES

Blue light reducer	yes
Flicker free	yes
Adaptive Sync support	HDMI: 1920 x 1080 @48-144Hz, DP: 1920 x 1080 @48-165Hz
OSD languages	EN, DE, FR, ES, IT, PT, RU, JP, CZ, NL, PL
Control buttons	Signal select/ Exit, +/ Volume, -/ i-Style Colour, Menu, Power
User controls	picture adjust (contrast, brightness, overdrive, ACR, ECO, blue light reducer, Black Tuner, MBR, gamma), input select, audio adjust (volume, mute), store user settings, colour settings (colour temperature, 6-Axis, user preset), image adjust (i-Style colour, X-Res Technology, sharp & soft, HDMI range, direct drive mode, video mode adjust), language, setup menu (OSD H. position, OSD V. position, OSD time out, opening logo, AMD FreeSync Premium, LED), display information, reset
Speakers	2 x 2W
Convenience	Kensington-lock™ prepared, DDC2B, Mac OSX



### 04 MECHANICAL

Display position adjustments	height, tilt, pivot (rotation both sides)
Height adjustment	130mm
Rotation (PIVOT function)	90°
Tilt angle	18° up; 3° down
VESA mounting	100 x 100mm
Cable management system	yes



Cables	power, USB, HDMI, DP
Other	quick start guide, safety guide

## 06 POWER MANAGEMENT


Power supply unit	internal
Power supply	AC 100 - 240V, 50/60Hz
Power usage	22W typical, 0.5W stand by, 0.3W off mode

# 07 SUSTAINABILITY

Regulations	CE, TÜV-Bauart, EAC, PSE, RoHS support, ErP, WEEE, VCCI, REACH
Energy efficiency class (Regulation (EU) 2017/1369)	E
,	above 0.1%; Lead
REACH SVHC	above 0.1%. Lead

## 08 DIMENSIONS / WEIGHT

Product dimensions W x H x D	612.5 x 416(546) x 256mm
Box dimensions W x H x D	745 x 480 x 204mm
Weight (without box)	5.2kg
Weight (with box)	7.5kg
EAN code	4948570117758



All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

© IIYAMA CORPORATION. ALL RIGHTS RESERVED