



### Red Eagle - join the PRO squad

Whether you already are or are aiming to be a hardcore gamer, the 24.5" G-MASTER GB2560HSU known as Red Eagle is the competitive edge you need to be able to unleash your full gaming potential. Armed with FreeSync technology, 165Hz refresh rate and a blistering 0.5ms MPRT response time you can make split second decisions and forget about ghosting effects or smearing issues. The ability to adjust brightness and the dark shades with the Black Tuner delivers greater viewing performance in shadowed areas. Nothing will skip your attention. Dual input setup (HDMI, DisplayPort), speakers, headphone connector and a 2.0 USB hub are all included. No matter which you prefer: RTS, FPS, MOBA and MMO – with the Red Eagle on your desk you are top of the gamer community food chain.



165Hz & 0.5ms MPRT

With 165Hz refresh rate and 0.5ms MPRT response time the force is with you! Make split second decisions and be sure the image on the screen is always sharp and smooth.



FreeSync™ Premium Technology

This monitor guarantees low input latency and low framerate compensation putting an end to any tearing or stuttering issues at virtually any framerate.



Diagonal	24.5", 62.2cm
Panel	TN LED, matte finish
Native resolution	1920 x 1080 @165Hz (2.1 megapixel Full HD)
Aspect ratio	16:9
Panel brightness	400 cd/m <sup>2</sup>
Static contrast	1000:1
Advanced contrast	80M:1
Response time (MPRT)	0.5ms
Viewing zone	horizontal/vertical: 170°/160°, right/left: 85°/85°, up/down: 80°/80°
Colour support	16.7mln
Horizontal Sync	31 - 184kHz
Viewable area W x H	543.74 x 302.61mm, 21.4 x 11.9"
Pixel pitch	0.283mm
Colour	matte, black



## 02 INTERFACES / CONNECTORS / CONTROLS

Signal input	HDMI x1 (v.2.0 max. 1920 x 1080 @165Hz) DisplayPort x1 (v.1.3 max. 1920 x 1080 @165Hz)
USB HUB	x2 (v.2.0 (DC5V, 500mA))
HDCP	yes
Headphone connector	yes



Blue light reducer	yes
Flicker free	yes
Adaptive Sync support	1920 x 1080 @40-165Hz
OSD languages	EN, DE, FR, ES, IT, RU, JP, CZ, NL, PL
Control buttons	Power, Menu/ Select, Scroll up/ Volume, Scroll down/ i-Style, Exit/ ECO, Input
User controls	picture adjust (contrast, brightness, OverDrive, ACR, ECO, Blue Light Reducer, Black Tuner, colour saturation, MBR, gamma), input select, audio adjust (volume, mute), store user settings, colour adjust (colour temperature, 6-Axis, user preset), image adjust (i-style Colour, X-Res Technology, sharp&soft, RGB range, video mode adjust), language, setup menu (OSD H. position, OSD V. position, OSD rotate, OSD time out, opening logo, FreeSync Premium, LED), display information, reset
Speakers	2 x 2W
Convenience	Kensington-lock™ prepared, DDC2B, Mac OSX



## 04 MECHANICAL

Display position adjustments	height, pivot (rotation), swivel, tilt
Height adjustment	130mm
Rotation (PIVOT function)	90°
Swivel stand	90°; 45° left; 45° right
Tilt angle	22° up; 5° down
VESA mounting	100 x 100mm
Cable management system	yes

# 05 ACCESSORIES INCLUDED

Cables	power, USB, HDMI
Other	quick start guide, safety guide

# 06 POWER MANAGEMENT


Power supply unit	internal
Power supply	AC 100 - 240V, 50/60Hz
Power usage	22W typical, 0.5W stand by, 0.26W off mode

# 07 SUSTAINABILITY

Regulations	CE, TÜV-GS, EAC, RoHS support, ErP, WEEE, EPEAT, REACH, UKCA
Energy efficiency class (Regulation (EU) 2017/1369)	F
REACH SVHC	above 0.1%; Lead
	45010 0.170. E044

# 08 DIMENSIONS / WEIGHT

Product dimensions W x H x D	557.5 x 370 (500) x 210mm
Box dimensions W x H x D	695 x 415 x 190mm
Weight (without box)	5.5kg
Weight (with box)	7.1kg
EAN code	4948570118656



All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

© IIYAMA CORPORATION. ALL RIGHTS RESERVED